



## TECHNICAL DATA SHEET

### PURPOSE

## PAINT REMOVER

REVISION DATE: July 2024  
(Supersedes all previous publications)



### PRODUCT INFORMATION

#### PRODUCT DESCRIPTION

**PAINT REMOVER** is a high strength coating remover for removing enamel, varnish and acrylic paints from various surfaces.

#### PRODUCT USES

To assist in the removal of old paint and varnishes during the surface preparation process. Suitable to remove alkyd, water and nitro cellulose-based paints.

### TECHNICAL INFORMATION

GENERIC TYPE  
SPREADRATE  
FLASH POINT  
COLOURS  
PACK SIZE  
STORAGE

Methylene Chloride  
1-2 m<sup>2</sup>/ℓ  
N/A – Highly volatile  
Semi-transparent  
500mℓ, 1ℓ and 5ℓ  
Store away from direct sunlight, heat and severely cold or damp conditions. Ensure that containers are properly sealed before storage.

### APPLICATION DETAILS

#### PRIOR TO USE

Mix well using a flat paddle until homogeneous in consistency.

#### APPLICATION METHOD

Brush only

#### THINNING

Do not thin

#### CLEANING OF EQUIPMENT

Warm water and Sabre Detergent Solution

#### DRYING TIME (@ 23°C & 55% RH)

N/A – Do not allow to dry. Keep wet contact.

*Note: higher temperatures will accelerate the drying times (approximately halved for every 10°C increase), whilst lower temperatures will retard the drying times (approximately doubled for every 10°C decrease).*

#### APPLICATION CONDITIONS

	MIN	MAX
Surface Temp (°C)	15 °C	40 °C
Ambient Temp (°C)	15 °C	40 °C
Relative Humidity	10%	75%
or 4°C minimum above dew point		

## SAFETY PRECAUTIONS

Ensure good ventilation during application and do not breathe in volatile fumes.  
Keep out of reach from children.  
In case of skin contact, wash with soap and water.  
In case of eye contact rinse immediately with running water and seek medical advice if eyes are irritated.  
Harmful if swallowed, do not induce vomiting and seek immediate medical attention.  
Always wear the appropriate protective clothing during product handling and application.  
Refer to Material Safety Data Sheet on our website for more detailed safety information.

---

## APPLICATION

---

### All Surfaces

Apply product generously in 0.5m<sup>2</sup> blocks at a time. Leave for 5-10 minutes to activate. Scrape residual product with a scraper or steel wool. Apply a second time if necessary. When done, wash the surface down and sand accordingly.

*Do not use this product in direct sunlight or warm areas as PAINT REMOVER is very volatile.*

**Please Note:** Use correct protective clothing at all time when handling the product. Use proper eye protection. The product should be applied in a well-ventilated area only as the volatile fumes could have negative effects on respiration. Refer to MSDS for more safety precautions.

---

## DISCLAIMER

---

*The technical information contained in this document are given in good faith and are meant to be used as a guideline by the specifier or user. Whilst we are confident about the quality of our products, we cannot accept any liability for the incorrect use or application of our products. Surface preparation forms an integral part of the scope of works and it is expected that the highest standards are maintained during surface preparation and application, to ensure that our products perform as intended. Always ensure to use the same product batch numbers, refrain from doing spot touch-ups and paint surfaces from corner to corner to prevent colour and sheen variance.*

Please note that all our latest Product Data Sheets and Material Safety Data Sheets are available for viewing on our website at [www.sabre.co.za](http://www.sabre.co.za)

**SABRE PAINTS (PTY) LIMITED**