



PAINT WITH CONFIDENCE



TECHNICAL DATA SHEET

PERFORMA PLUS ALKALI RESISTANT SEALER

REVISION DATE: November 2018
(Supersedes all previous publications)

PRODUCT INFORMATION

PRODUCT DESCRIPTION

AR SEALER is a high-performance, moisture tolerant and highly alkali-resistant primer to penetrate and seal various raw, new and previously painted surfaces like masonry, gypsum, porous and chalked surfaces.

PRODUCT USES

To penetrate and seal cement plaster, concrete, brick, gypsum plaster, fibre-cement, various building boards, chalked paint and lime washed surfaces in preparation for top coats.

BENEFITS & FEATURES

- Formulated for excellent penetration.
- Excellent barrier against highly alkali substrates.
- Seals porous surfaces and binds chalked surfaces.
- Can be used as a barrier coat to block unwanted stains.
- Excellent obliteration.

TECHNICAL INFORMATION

GENERIC TYPE

Thermoplastic acrylate copolymer

FINISH

Matt

VOLUME SOLIDS

40± 1%

SPECIFIC GRAVITY

1.22kg/litre (typical)

RECOMMENDED DFT

50 - 65 microns. One coat required.

RECOMMENDED WFT

125 - 160 microns. One coat required

SPREAD RATE

Smooth Surface	Rough Surface
6 – 8 m ² /ℓ	4 - 6 m ² /ℓ
Surface porosity, profile, application tools and technique will affect practical spread rate	

LEAD FREE

Yes

FLASH POINT

38°C

COLOURS

White

PACK SIZE

1ℓ, 5ℓ and 20ℓ

STORAGE

Store away from direct sunlight, heat and severely cold or damp conditions. Ensure that containers are properly sealed before storage.



DIRECTORS: K. POOL (MANAGING), C. STRYDOM,
W. SCHMIDT, K. STRYDOM, J. BATIST | REG. NO. 1979/006655/07



