



PAINT WITH CONFIDENCE

SABRE PAINTS (PTY) LTD | 55 TREDOUX STREET, BEACONVALE, PAROW, SOUTH AFRICA | P.O.BOX 459, PAROW, 7499  
T: 021 931 7231 | F: 021 933 4755 | PAINT@SABRE.CO.ZA | WWW.SABRE.CO.ZA

# SAFETY DATA SHEET

Issue date: 07 May 2019

Page 1/5

## Section 1: Identification

**Product Name:** EPOXY FLOOR COAT-BASE

**Product Code:** 7.8G-BASE

**Chemical Name/Synonyms:** WATER BASED EPOXY

**Company:** SABRE PAINTS(PTY)LTD,55 TREDOUX STREET,BEACONVALE,PAROW,SOUTH AFRICA

**In emergency call:** 021-931 7231

**For information about this SDS:** phone#: 021-931 7231, e-mail:admin@sabre.co.za

## Section 2: Hazard(s) Identification

### Hazard Classification:

Harmful if swallowed.

Risk of serious damage to eyes.

Irritating to respiratory system and skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

**Signal Word(s):** Warning

### Hazard Statements:

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

### Pictograms:



**Precautionary Statements:** Keep out of reach of children. If medical advice is needed, have product container or label at hand. Wear protective clothing.

**Other hazards which do not result in classification:** No data available

**Section 3: Composition/ Information on Ingredients**

Chemical Name	Synonym	CAS#	Conc.
Amine Curing agent	Epoxy amine	Proprietary	50-60%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

**Section 4: First-Aid Measures**

**After skin contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watch bands.

**After eye contact:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately. Chemical burns must be treated promptly by a physician.

**After inhalation:** Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**After swallowing:** If swallowed, wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

**Section 5: Fire-Fighting Measures**

**Suitable extinguishing agents:** Fog or Foam, CO<sub>2</sub>, Dry chemical powder. Do NOT use water jets

**Unsuitable extinguishing media:** Do not use direct water stream. May spread fire.

**Special protective equipment for firefighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Hazardous combustion products:** No specific data.

**Section 6: Accidental Release Measures**

**Personal precautions:** Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**Measures for environmental protection:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

**Measures for cleaning/collecting:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.



## Section 7: Handling and Storage

**Handling:** Put on appropriate personal protective equipment Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating and drinking. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Spills of these organic materials on hot fibrous insulations may lead to lowering of the auto ignition temperatures possibly resulting in spontaneous combustion. Do not reuse container.

**Storage:** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

## Section 8: Exposure Controls/Personal Protection

**Appropriate engineering controls:** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**General protective and hygienic measures:** Use respirator and eye protection.

**Breathing equipment:** In case of insufficient ventilation, use suitable respiratory protection.

**Body protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Protection of hands:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times. Consider the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

**Other skin protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:** Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Eye/face protection:** Chemical splash goggles. Avoid direct contact.

## Section 9: Physical and Chemical Properties

**Form:** Viscous Liquid

**Odor:** Mild to sweet

**Odor threshold:** n/d

**Flash point:** >100 deg Celcius

**Relative density:** approximately 1.2

**Solubility in/Miscibility with water:** Soluble

## Section 10: Stability and Reactivity

**Reactivity:** Stable under normal conditions.

**Chemical stability:** Product is stable.

**Possibility of hazardous reactions:** Under normal conditions of storage and use, no hazardous reaction will occur.

**Conditions to avoid:** Stable under normal conditions.

**Incompatible materials:** No specific data.

**Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced. Reacts with considerable heat release with some curing agents.



**Section 11: Toxicological Information**

**Acute toxicity:** No applicable toxicity data.  
**Potential acute health effects:**  
**Inhalation:** May cause respiratory irritation.  
**Ingestion:** Harmful if swallowed  
**Skin contact:** Irritating to respiratory system and skin.  
**Eye contact:** Risk of serious damage to eyes.  
**Carcinogenicity:** No known significant effects or critical hazards.  
**Mutagenicity:** No known significant effects or critical hazards.  
**Teratogenicity:** No known significant effects or critical hazards.  
**Developmental effects:** No known significant effects or critical hazards.  
**Fertility effects:** No known significant effects or critical hazards.

**Section 12: Ecological Information**

**Ecotoxicity:** No data available.  
**Mobility:** Not available.  
**Biodegradation:** Not available.  
**Bioaccumulation:** Not available.  
**Other adverse effects:** No known significant effects or critical hazards.

**Section 13: Disposal Considerations**

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**Section 14: Transport Information**

**UN number:** UN1263  
**Transport Hazard class:** 3  
**Packaging group:** III  
**Special precautions for user:** Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Section 15: Regulatory Information**

Safety, health and environmental regulations/legislation specific for the substance or mixture  
EU Regulation (EC) No. 1907/2006 (REACH)  
List of substances subject to authorisation: None of the components are listed.  
Substances of very high concern: None of the components are listed.  
Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not applicable  
Other national and international regulations: Not listed



**Section 16: Other Information****Key to abbreviations :**

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

**Full text of abbreviated H statements**

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*

